



WAAS CH 90509 W14A	APP CRS 144°	Rwy ldg 13503 TDZE 1169 Apt Elev 1189
--	------------------------	--

RNAV (GPS) Y RWY 14L

GRANT COUNTY INTL (MWH)

RNP APCH.			MISSED APPROACH: Climb to 4000 direct HEDBI and on track 124° to UPBOB and hold.	
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C. ▲ Baro-VNAV and VDP NA when using Ephrata altimeter setting. When local altimeter setting not received, use Ephrata altimeter setting; increase all DA 36 feet and all MDA 40 feet, increase LNAV/VNAV visibility all Cats ⅓ SM, LNAV Cats C and D and Circling Cat D ¼ SM.				
ATIS 119.05	GRANT COUNTY APP CON ★ 126.4 379.95	GRANT COUNTY TOWER ★ 118.25 (CTAF) 0 257.8 (EAST) 128.0 257.8 (WEST)	GND CON 121.9	UNICOM 122.95



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).		4000	HEDBI	tr 124°	UPBOB
Holding Pattern		4000	324°	144°	3000
GP 3.00° TCH 52		3000	144°	1780	1.1 NM to RW14L
CATEGORY	A	B	C	D	
LPV DA		1369-¾	200 (200-¾)		
LNAV/VNAV DA		1436-⅞	267 (300-⅞)		
LNAV MDA	1580-1	411 (400-1)	1580-1½	411 (400-1½)	
CIRCLING	1660-1	471 (500-1)	1680-1½	1820-2	631 (700-2)