

WAAS
CH **86903**
W26A

APP CRS
272°

Rwy Idg **8600**
TDZE **9**
Apt Elev **9**


RNAV (GPS) RWY 26R
MIAMI INTL (MIA)

RNP APCH - GPS.


Simultaneous approach authorized. LNAV procedure NA during simultaneous operations.
Use of FD or AP required during simultaneous operations.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 9°C or above 54°C.





MISSED APPROACH: Climb to 800 then climbing right turn to 4000 direct BRBRA and hold, continue climb-in-hold to 4000.

D-ATIS	MIAMI APP CON	MIAMI TOWER	GND CON	CINC DEL	CPDLC
ARR 119.15 DEP 133.675	124.85 322.3	118.3 256.9	121.8 (Rwys 8L/R, 12, 26L/R) 127.5 (Rwys 9, 27, 30)	348.6 135.35	



ELEV 9	D	TDZE 9
--------	---	--------



800	4000	BRBRA				
						
						
CATEGORY	A		B	C	D	
LPV DA			265- $\frac{3}{4}$	256 (300- $\frac{3}{4}$)		
LNAV/VNAV DA			432-1 $\frac{1}{4}$	423 (500-1 $\frac{1}{4}$)		
LNAV MDA	480-1	471 (500-1)	480-1 $\frac{3}{8}$		471 (500-1 $\frac{3}{8}$)	