

WAAS CH 86640 W14A	APP CRS 144°	Rwy Idg TDZE Apt Elev	5000 18 18
--	------------------------	-----------------------------	---------------------------------------


RNAV (GPS) RWY 14

PLATINUM (PTU)(PAPM)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Togiak altimeter setting. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Togiak altimeter setting: increase LPV DA to 371 feet; increase LNAV/VNAV DA to 424 feet and all Cats visibilities ¾ SM; increase all MDA 120 feet and increase LNAV and Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 420 then Climbing right turn to 2500 direct FELTI and hold.

AWOS-3P 118.375	ANCHORAGE CENTER 124.2 251.1	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



ELEV 18

TDZE 18

144° to RWY14

5000 x 7.5

32

MIRL Rwy 14-32 0

				420	2500	FELTI		
2500 ← 324° 144° → 144° 1700				JEPRU 2.1 NM to RW14		*1.1 NM to RW14	*LNAV only	
GP 3.00° TCH 40				5.8 NM		3.1 NM	1 NM	1.1 NM
CATEGORY	A		B		C		D	
LPV DA	268-1		250 (300-1)				NA	
LNAV/ VNAV DA	321-1		303 (400-1)				NA	
LNAV MDA	400-1		382 (400-1)		400-1 1/8 382 (400-1 1/8)		NA	
CIRCLING	460-1 442 (500-1)		480-1 462 (500-1)		520-1 1/2 502 (600-1 1/2)		NA	

AK, 15 JUN 2023 to 10 AUG 2023

AK, 15 JUN 2023 to 10 AUG 2023