

WAAS

CH **99535**

**W36A**

APP CRS

**002°**

Rwy Idg

**3197**

TDZE

**337**

Apt Elev

**337**

**RNAV (GPS) RWY 36**

OKOLONA MUNI/RICHARD STOVALL FLD (5A4)

Baro-VNAV NA. DME/DME RNP-0.3 NA. Use Tupelo altimeter setting; when not received, use Columbus Air Force Base altimeter setting and increase all DA 41 feet and all MDA 60 feet; increase LNAV/VNAV all Cats visibility ¼ mile and LNAV Cat C visibility ¼ mile.

Rwy 36 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:

Climb to 2600 direct

AYUDI and hold.

COLUMBUS APP CON ★

**126.075 229.15**

CTAF

**122.9 0**

MISSED APCH FIX

4 NM

182°

002°

AYUDI

RW36

690

560

748

(FAF) IXREW

2000

(6-7)

(IF/IAF) MUMDE

182°

002°

4 NM

2310

30 NM to MUMDE

3400

MUMDE

092°

272°

6 NM to MUMDE

2000

30 NM to MUMDE (NoPT)

3400

ELEV 337

TDZE 337

MIRL Rwy 18-36

81

3197 X 60

36

002° to RW36

2600

AYUDI

IXREW

2000

MUMDE

4 NM Holding Pattern

182°

002°

2000

GP 3.30°

TCH 55

4.6 NM

6.7 NM

CATEGORY	A	B	C	D
LPV DA	624-1 287 (300-1)			NA
LNAV/VNAV DA	732-1½ 395 (400-1½)			NA
LNAV MDA	860-1 523 (600-1)	860-1½ 523 (600-1½)		NA
CIRCLING	920-1 583 (600-1)	1080-2¼ 743 (800-2¼)		NA

OKOLONA, MISSISSIPPI

Amdt 1A 15SEP16

34°-01'N - 88°44'W

OKOLONA MUNI/RICHARD STOVALL FLD (5A4)

**RNAV (GPS) RWY 36**