



WAAS CH 53509 W09A	APP CRS 091°	Rwy Idg TDZE 530 Apt Elev 530
--	------------------------	---

RNAV (GPS) RWY 9
PEKIN MUNI (C15)

RNP APCH-GPS	Baro-VNAV NA. Rwy 9 helicopter visibility reduction below ¾ SM NA. Use General Downing - Peoria Intl altimeter setting; when not received, use Lincoln altimeter setting; increase LPV DA to 887 feet; increase LNAV/VNAV DA to 1007 feet; increase all MDAs 40 feet and visibility Cat C and D ¼ SM.	MISSED APPROACH: Climb to 2500 direct WURID and hold.
--------------	--	--

SAINT LOUIS APP CON 125.8 269.2	UNICOM 122.8 (CTAF) 1
---	---------------------------------



ELEV 530	TDZE 530
REIL Rwy 9 and 27 1	
MIRL Rwy 9-27 1	

CATEGORY	A	B	C	D
LPV DA	862-1 332 (400-1)			
LNAV/VNAV DA	982-1 3/8 452 (500-1 3/8)			
LNAV MDA	940-1 410 (500-1)	940-1 1/8 410 (500-1 1/8)		
CIRCLING	1060-1 530 (600-1)	1100-1 1/2 570 (600-1 1/2)	1360-2 3/4 830 (900-2 3/4)	

EC-3, 13 JUL 2023 to 10 AUG 2023

EC-3, 13 JUL 2023 to 10 AUG 2023