
WAAS Rwy Idg TDZE 4008 APP CRS CH 57901 3210 W32A Apt Elev

RNAV (GPS) RWY 32 JACKSONVILLE EXEC AT CRAIG (CRG)

Night landing: Rwy 5 NA. Baro-VNAV and VDP NA when using Jacksonville Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C (27°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction MALSR below 3/4 SM NA. VDP NA with Jacksonville Intl altimeter setting. When local altimeter setting not received, use Jacksonville Intl altimeter setting: increase LPV DA to 273 feet; increase LNAV/VNAV DA to 413 feet; increase all MDAs 40 feet and Circling visibility Cat C ¼ SM. For inop MALSR, when using Jacksonville Intl altimeter setting, increase LNAV/VNAV all Cats visibility to 11/8 and LNAV Cats C/D visibility to 11/4.

MISSED APPROACH: Climb to 700 then climbing right turn to 1900 direct JEVAG and hold.

CRAIG TOWER * ATIS JACKSONVILLE APP CON GND CON CLNC DEL UNICOM 125.4 124.9 308.4 132.1 (CTAF) 0 269.525 121.8 118.35 122.95



13 JUL 2023 to 10 AUG 2023