

WAAS CH 86431 W23A	APP CRS 227°	Rwy Idg TDZE Apt Elev 5000 429 441
--	------------------------	--


RNAV (GPS) RWY 23

NORTH CENTRAL STATE (Sf'Z)

⚠ Circling Rwy 15, 33 NA at night. Baro-VNAV NA when using Providence altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. VDP NA with Providence altimeter setting. When local altimeter setting not received, use Providence altimeter setting and increase all DA 82 feet and all MDA 100 feet; increase LPV all Cats visibility to 1¼, LNAV/VNAV all Cats visibility to 1¾ and LNAV Cat C visibility to 1¾. Rwy 23 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2600 direct WALLU and hold.

AWOS-3PT 120.775	PROVIDENCE APP CON ★ 123.675 244.875	CLNC DEL 124.35	UNICOM 123.075 (CTAF) 0
----------------------------	--	---------------------------	-----------------------------------



4 NM 227° 047°

1148 A

2600 ↑

WALLU

LIVGE
3 NM to
RW23

RUSEL
2300

KENPY
2500

* LNAV only.

RW23

* 1.2 NM to RW23

1400*

227°

2300

GP 3.00° TCH 35

1.2 NM
1.8 NM
2.8 NM
6.3 NM

CATEGORY	A	B	C	D
LPV DA	679-7/8	250 (300-7/8)		NA
LNAV/VNAV DA	849-1½	420 (500-1½)		NA
LNAV MDA	820-1 391 (400-1)	820-1½ 391 (400-1½)		NA
C CIRCLING	900-1 459 (500-1)	900-1½ 459 (500-1½)		NA

ELEV 441

TDZE 429

227° to RW23