SC-4, 13 JUL 2023 to 10 AUG 2023

## RNAV (GPS) RWY 5

COLUMBIA/MARION COUNTY (ØRØ)

RNP APCH - GPS. 

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Hattiesburgh/Laurel Rgnl altimeter setting and increase all DA 66 feet and all MDA 80 feet; increase LPV all Cats visibility  $\frac{1}{8}$  mile and LNAV/VNAV all Cats and Circling Cat C visibilities  $\frac{1}{2}$  mile, increase Circling Cat D visibility  $\frac{1}{2}$  mile, increase LNAV Cat C and D visibility  $\frac{9}{8}$  mile. VDP and Baro-VNAV NA when using Hattiesburgh/Laurel Rgnl altimeter setting. Rwy 5 helicopter visibility reduction below  $\frac{3}{4}$  SM NA

MISSED APPROACH: Climb to 2400 direct NERAE and hold.

AWOS-3PT **HOUSTON CENTER** UNICOM 120,675 122.8 (CTAF) 126.8 327.8 8 HULNA NERAE **∧** 673 ó **∧**862 2400 **CECAK** 30 (NoPT) 14 2 NM to RW05 2400 05 1,528 <sup>933</sup>∧ **∧**823 1,662 HULNA (FAF) zòsog (IF/IAF) HULNA 270 255 **ELEV** TDZE 4 NM 2400 NERAE 4 NM HULNA Holding Pattern **ZOSOG** CECAK 2 NM to \*LNAV only **RW05** 1500 \*1.5 NM 0540, to RW05 RW05 4 1500 GP 3.00° 920 TCH 40 +1.8 NM + 0.5 NM 1.5 NM 6.1 NM CATEGORY 505-7/8 LPV DA 250 (300-%) 054° to **RW05** LNAV/ 743-1% DΑ 488 (500-1%) VNAV 760-1% 505 (500-1%) LNAV MDA 760-1 505 (500-1) 760-1 820-1 920-13/4 1000-21/4 REIL Rwy 5 and 230 **C** CIRCLING 490 (500-1) 730 (800-21/4) MIRL Rwy 5-23 0 550 (600-1) 650 (700-134)

COLUMBIA, MISSISSIPPI

COLUMBIA/MARION COUNTY ( $\emptyset R \emptyset$ ) RNAV (GPS) RWY 5

31°18′N-89°49′W