

WAAS CH 53719 W02A	APP CRS 022°	Rwy Idg TDZE Apt Elev	4400 1068 1068
--	------------------------	-----------------------------	---



RNAV (GPS) RWY 2
GRIMES FLD (I74)

RNP APCH.

▼ Baro-VNAV and VDP NA when using Springfield altimeter setting. Rwy 2 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Springfield altimeter setting and increase all DAs 44 feet, all MDAs 60 feet, increase LNAV/VNAV all Cats visibility ¼ SM, and increase Circling Cat C visibility ¼ SM. Circling NA to Rwy 1 and 19.

⚠ MISSED APPROACH: Climb to 3000 direct HIRID and hold.

AWOS-3 118.325	COLUMBUS APP CON 118.425 294.5	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------------------



4 NM Holding Pattern				SEBUE	RIKOE	3000	*LNAV only.	3000	HIRID
6000 4000				← 202° 022° →	022°	3000	WANIS 2.4 NM to RWY 2	↑	✦
GP 3.00° TCH 44						3000	*1.3 NM to RWY 2		
CATEGORY	A	B	C	D					
LPV DA	1318-1		250 (300-1)		NA				
LNAV/VNAV DA	1501-1½		433 (500-1½)		NA				
LNAV MDA	1500-1		432 (500-1)		1500-1¼ 432 (500-1¼)				
CIRCLING	1580-1 512 (600-1)		1780-1 712 (800-1)		1800-2 732 (800-2)				