

WAAS CH <b>40433</b> <b>W23A</b>	APP CRS <b>234°</b>	Rwy Idg TDZE Apt Elev	<b>3601</b> <b>3204</b> <b>3204</b>
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 23


RAPID CITY RGNL (RAP)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C (-5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Ellsworth AFB altimeter setting and increase all DA 25 feet and all MDA 40 feet. VDP and Baro-VNAV NA when using Ellsworth AFB altimeter setting.

MISSED APPROACH: Climbing left turn to 5300 direct EWEBU and hold.

ASOS <b>118.525</b>	ELLSWORTH APP CON ★ <b>119.5 259.1</b>	RAPID CITY TOWER ★ <b>125.85 (CTAF) 0 257.8</b>	GND CON <b>121.9</b>	UNICOM <b>122.95</b>
------------------------	---	--	-------------------------	-------------------------



ELEV 3204

TDZE 3204

5300 EWEBU

\*LNAV only.

\*1 NM to RW23

1.9 NM to RW23

3820\*

1 NM

0.9 NM

3 NM

4 NM

YUKUR

4800

234°

054°

4800

GP 3.00°

TCH 38

CATEGORY	A	B	C	D
LPV DA	3454-1	250 (300-1)		NA
LNAV/VNAV DA	3454-1	250 (300-1)		NA
LNAV MDA	3560-1	356 (400-1)		NA
CIRCLING	3660-1 456 (500-1)	3840-1 636 (700-1)		NA

3224

TWR 3233

REIL Rwy 14

MIRL Rwy 5-23

HIRL Rwy 14-32

234°

054°

0.6% DOWN

0.8% UP

0.5% UP

3601 X 75

8201 X 150

3232