

APP CRS
037°

Rwy Idg
4313

TDZE
13

Apt Elev
19

RNAV (GPS) RWY 4

CHARLESTON EXEC (JZI)

▼

▲

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting and increase all MDAs 40 feet; increase LNAV Cat D and Circling visibility Cats C/D ¼ SM.

MISSED APPROACH: Climbing left turn to 2000 direct HONAP and hold.

AWOS-3 123.775	CHARLESTON APP CON 120.7 306.925	CLNC DEL 119.85	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------	---------------------------------

VGSI and descent angles not coincident.

2000 HONAP

▲

COSOM

AVEGE

CUDUL 2.2 NM to RW04

RW04

1700

066°

1700

037°

740

3.04° TCH 40

6 NM

2.9 NM

2.2 NM

Procedure Turn NA

CATEGORY	A	B	C	D
LNAV MDA	420-1	407 (500-1)	420-1¼	407 (500-1¼)
CIRCLING	460-1 441 (500-1)	480-1 461 (500-1)	860-2½ 841 (900-2½)	860-2¾ 841 (900-2¾)

ELEV 19

TDZE 13

6

5350 X 100

27

4313 X 150

037° to RW04

REIL Rwy 9 and 27 0

MIRL Rwy 4-22 0

HIRL Rwy 9-27 0

CHARLESTON, SOUTH CAROLINA
Orig-A 17JUN21

32°42'N-80°00'W

CHARLESTON EXEC (JZI)
RNAV (GPS) RWY 4