



WAAS CH 42600 W04A	APP CRS 043°	Rwy Idg TDZE Apt Elev	5764 2634 2634
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 4
FRANK WILEY FLD (MLS)

RNP APCH-GPS. ▼ Baro-VNAV and VDP NA when using Glendive altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. When local altimeter setting not received, use Glendive altimeter setting: increase LPV and LNAV/VNAV DA to 3051 and all visibilities ½ SM. Increase all MDA 180 feet and LNAV Cat C and D visibilities ½ SM and Circling Cat C and D visibilities ½ SM.		MISSED APPROACH: Climb to 6000 direct AXUPE and hold, continue climb-in-hold to 6000.
--	--	---

ASOS 135.575	SALT LAKE CENTER 126.85 305.2	UNICOM 123.0 (CTAF)
------------------------	---	-------------------------------



CATEGORY	A	B	C	D
LPV DA	2884-1		250 (300-1)	
LNAV/VNAV DA	2884-1		250 (300-1)	
LNAV MDA	3040-1	406 (500-1)	3040-1½	406 (500-1½)
CIRCLING	3060-1 426 (500-1)	3100-1 466 (500-1)	3160-1½ 526 (600-1½)	3320-2¼ 686 (700-2¼)



NW-1, 13 JUL 2023 to 10 AUG 2023

NW-1, 13 JUL 2023 to 10 AUG 2023