

WAAS
CH **40301**
W35A


APP CRS
348°

Rwy Idg
TDZE **21**
Apt Elev **24**

RNAV (GPS) RWY 35

ACADIANA RGNL (A.R.A.)

RNP APCH.				MALSR	MISSED APPROACH: Climb to 440 then climbing right turn to 2000 direct LULEW and hold.		
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -3°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ½ SM and LNAV Cats C/D visibility to 1 SM. Circling NA to Rwys 17W and 35W.							
ASOS	LAFAYETTE APP CON★	ACADIANA TOWER★	GND CON	CLNC DEL	CLNC DEL	UNICOM	★
133.325	121.1 268.7	125.0 (CTAF) 0 239.3	121.7	121.7	118.05 (when twr closed)	122.95	122.7



440	2000	LULEW	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 52).		4 NM
*LNAV only.		ISUCE	Holding Pattern		
RW35		WOKDO 2.2 NM to RW35	1700		
1 NM		*1 NM to RW35	760*		
1.2 NM		2.9 NM	8 NM		
CATEGORY	A	B	C	D	
LPV DA	221-½		200 (200-½)		
LNAV/DA	303-½		282 (300-½)		
LNAV MDA	380-½		380-¾		359 (400-¾)
CIRCLING	440-1		480-1		600-1½
	416 (500-1)		456 (500-1)		576 (600-½)
					680-2
					656 (700-2)

