13 JUL 2023 to 10 AUG 2023

SW-4.

WAAS Rwy Idg 4870 APP CRS CH 93544 TDŻE 1240 038° Apt Elev W04A

RNAV (GPS) RWY 4R

CHANDLER MUNI (CHD) RNP APCH - GPS. MISSED APPROACH: (Do not exceed 210K until DECTU) Climb For uncompensated Baro-VNAV systems, LNAV/VNAV to 2200 then climbing right turn to 4000 direct to DECTU and hold NA below -17°C or above 54°C. CHANDLER TOWER * ATIS PHOENIX APP CON GND CON UNICOM 126.1 (CTAF) 0 133.1 128.325 123.7 363.0 124.4 122.95 (North and West) (South and East Procedure NA for arrivals at PXR VORTAC PXR on V16 and T306 east bound. 3068 ⚠ ۸¹⁴⁴¹ **∧**1394 (IAF) SIZVU (FAF) KEDDĹ 4354 . 3104 (IF) DEC RW04R 25 Ny 6200 4 NM \bigcirc (IAF) NISIW 1243 TDZE 1240 STANFIELD TFD 2200 4000 DECTU DECTU **KEDDU** 4000 2900 1.1 NM to 039₀ RW04R RW04R 2900 GP 3.00° TCH 39 5.2 NM -4 NM-1.1 NM CATEGORY D 1269± LPV DA 1490-3/4 250 (300-3/4) NA 038° to RW04R LNAV/ DA 1640-11/8 400 (400-11/8) NA VNAV 1640-11/8 LNAV MDA 1640-1 400 (400-1) NA 400 (400-11/8) REIL Rwys 4R and 22L 1

CHANDLER, ARIZONA Amdt 1 02DEC21

C CIRCLING

1700-1

457 (500-1)

1760-1

517 (600-1)

CHANDLER MUNI (CHD) RNAV (GPS) RWY 4R

MIRL Rwys 4L-22R and 4R-22L 1

NA

1760-11/2

517 (600-11/2)