SW-1, 13 JUL 2023

ō

10 AUG 2023

RNAV (GPS) RWY 13

Rwy Idg TDZE 8196 APCH CRS 4294 128° CANNON AFB (KCVS) AL-512 (USAF) Arpt Elev 4295 RNP APCH SSALR MISSED APPROACH: Climb to 7000 direct HOMEP, * When ALS inop increase vis to 1 3/8 miles. ** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 1/2 miles then track 128° to SOPLE and hold. (A3) ATIS CANNON APP CON **TOWER** GND CON CLNC DEL 119.1 269.9 118.425 352.1 120.4 270.25 121.9 275.8 120.2 293.225 4974 For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -23°C or above 54°C. HOLD 14,000 ҈∆5074 4751 7000 (IAF) 7ÙNÉN 8000 ∧ ∧ 4922 4959 SP RW13 25 Ny 4610 RÁPKE **∧** 4785 6600 \Diamond (FAF) LERAY MISSED APPROACH ~ 4 NM SOPLE HOLD 10,000 °,∞ HOMEP EMERG SAFE ALT 100 NM 9000 7000 VGSI and RNAV glidepath not coincident (VGSI Angle 7000 ELEV 4295 TDZE 4294 SOPLE HOME **RAPKE** 3.00/TCH 37). 128° 7000 1280 BCN LERAY 4433 1.5 NM to 128° RW13 **RW13** (A₃) 5900 0 (P) GP 3.04° TCH 45 CATEGORY LNAV/VNAV DA* 4766-1 472 (500-1)LNAV MDA** 4820-1/2 526 (600-1/2) 4820-1 526 (600-1)4860-11/2 5000-21/4 5020-21/2 4840-1 545 (600-1) **C** CIRCLING 565 705 725 (600-11/2) (800-21/4) $(800-2\frac{1}{2})$ HIRL all Rwys

CLOVIS, NEW MEXICO

34°23'N - 103°19'W

CANNON AFB (KCVS)