5151 Rwy Idg APP CRS TDŹE 319 184° Apt Elev 344

## RNAV (GPS) RWY 18

Procedure NA for arrival

RW 18 25 Nz

3400


**(** 

TDZE 319

## READING RGNL/CARL A SPAATZ FLD (RDG)

Night landing: Rwy 18, 31 NA. DME/DME RNP-0.3 NA. Helicopter visibility MISSED APPROACH: Climb to reduction below 1 SM NA. When local altimeter setting not received, use 3000 direct COTAX and via 258° A Harrisburg Intl altimeter setting and increase all MDAs 100 feet, and increase track to BOYER and hold, LNAV Cat B visibility ¼ SM and Cat C and D visibility ½ SM, and increase continue climb-in-hold to 3000. Circling Cats B and C visibility 1/4 SM.

**ATIS** READING APP CON \* READING TOWER ★ **GND CON UNICOM** 127.1 125.15 257.9 121.9 122.95 119.9 (CTAF) **0** 288.3



806±

521 **∆** 

639±∧ ∧

 $\Lambda$  640

RW18

∧<sup>461±</sup>

COTAX


1070 \Lambda

**∆** 1351

**ELEV** 344


۸<sup>1263</sup>

1102



. 1390

Λ 1420



READING, PENNSYLVANIA Orig-B 20MAY21

READING RGNL/CARL A SPAATZ FLD  $\left(RDG\right)$ 

HIRL Rwys 13-31 and 18-36

40°23′N - 75°58′W