


WAAS CH 42834 W21A	APP CRS 215°	Rwy Idg 7001 TDZE 1047 Apt Elev 1078
--	------------------------	---

RNAV (GPS) RWY 21
TOPEKA RGNL (FOE)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F).
⚠ When local altimeter setting not received, use Philip Billard Muni altimeter setting and increase all DA 45 feet and all MDA 60 feet, increase LPV and LNAV/VNAV all Cats visibility to 1 mile and increase LNAV Cat C/D visibility and Circling Cat D visibility ½ mile. DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Philip Billard Muni altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 3000 direct
IDJOP and hold.

ATIS 128.25	KANSAS CITY CENTER 123.8 343.7	FORBES TOWER* 120.8 (CTAF) 0 340.2	GND CON 118.425 275.8	UNICOM 122.95
----------------	-----------------------------------	---------------------------------------	--------------------------	------------------



REIL Rwy 3, 13 and 21
MRL Rwy 3-21
HIRL Rwy 13-31