

WAAS  
CH **63136**  
**W30A**

APP CRS  
**307°**

Rwy Idg  
TDZE **4444**  
Apt Elev **4457**

**RNAV (GPS) RWY 30**

LAS CRUCES INTL (LRU)

**⚠**

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 51°C (124°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Deming altimeter setting. When local altimeter setting not received, use Deming altimeter setting: increase LPV DA to 4758 feet, LNAV/VNAV DA to 4863 feet and all visibilities  $\frac{3}{8}$  mile; increase all MDA 120 feet and visibility Cat C and D  $\frac{1}{2}$  mile.

MALSR

MISSED APPROACH: Climb to 9000 direct IPATE and hold, continue climb-in-hold to 9000.

AWOS-3 <b>119.025</b>	ALBUQUERQUE CENTER <b>128.2 285.5</b>	UNICOM <b>122.7 (CTAF) 0</b>
--------------------------	--	---------------------------------

MISSED APCH FIX

MSA RW30 25 NM

ELEV <b>4457</b>	<b>D</b>	TDZE <b>4444</b>
------------------	----------	------------------

REIL Rwy 12

HIRL Rwy 12-30 0

MIRL Rwy 4-22 and 8-26 0

9000	IPATE				MENDZ
		JOSP0			7000
		6400			6400
		1.1 NM	4.9 NM	4.9 NM	
					GP 3.00° TCH 47
CATEGORY	A	B	C	D	
LPV DA	4644- $\frac{1}{2}$		200 (200- $\frac{1}{2}$ )		
LNAV/VNAV DA	4749- $\frac{5}{8}$		305 (300- $\frac{5}{8}$ )		
LNAV MDA	4840- $\frac{1}{2}$ 396 (400- $\frac{1}{2}$ )		4840- $\frac{5}{8}$ 396 (400- $\frac{5}{8}$ )		
<b>C</b> CIRCLING	4900-1 443 (500-1)	5040-1 583 (600-1)	5320-2 $\frac{1}{2}$ 863 (900-2 $\frac{1}{2}$ )	5320-2 $\frac{3}{4}$ 863 (900-2 $\frac{3}{4}$ )	

LAS CRUCES, NEW MEXICO

Amdt 2 18AUG16

32°17'N-106°55'W

LAS CRUCES INTL (LRU)

**RNAV (GPS) RWY 30**