

WAAS

CH **61200**

W18A

APP CRS

186°

Rwy Idg

7001

TDZE

84

Apt Elev

89

RNAV (GPS) RWY 18

ALEXANDRIA INTL (AEX)

▼

⚠

DME/DME RNP-0.3 NA. Radar required when R-3801 A-B in use. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (119°F). Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 4000 direct HIPKU and via 105° track to MUSHE and hold.

ASOS	POLK APP CON	ALEXANDRIA TOWER	GND CON	CLNC DEL
123.975	125.4 254.8	127.35 (CTAF) 269.2	121.9 372.0	121.9

ELEV 89

D

TDZE 84

186° to RW18

3000 (24.9)

5 NM

106°

286°

MUSHE

4000

HIPKU

tr 105°

MUSHE

5 NM Holding Pattern

LATIW

000°

2600

GP 3.00°

TCH 55°

*LNAV only.

*1.2 NM to RW18

AQEKO

186°

1700

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 79).

1.2

3.6 NM

6.1 NM

CATEGORY	A	B	C	D
LPV DA	395-1 311 (400-1)			
LNAV/VNAV DA	539-1½ 455 (500-1½)			
LNAV MDA	520-1	436 (500-1)	520-1¼ 436 (500-1¼)	520-1½ 436 (500-1½)
CIRCLING	540-1 451 (500-1)	560-1 471 (500-1)	700-1¾ 611 (700-1¾)	860-2½ 771 (800-2½)

REIL Rwy 18, 32 and 36

HIRL Rwy 18-36 and 14-32

ALEXANDRIA, LOUISIANA

Amdt 1B 25MAR21

31°20'N-92°33'W

ALEXANDRIA INTL (AEX)

RNAV (GPS) RWY 18