SC-3,

13 JUL 2023 to

10 AUG 2023

WAAS 8505 Rwy Idg APP CRS CH 69430 TDZE 770 217º Apt Elev **W22A** 809

RNAV (GPS) Y RWY 22

SAN ANTONIO INTL (SAT) For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Circling NA west of Rwys 4 MISSED APPROACH: Climb to 3100 direct IMIKE and track 137° to EMBOW and hold. and 13R. DME/DME RNP-0.3 NA. SAN ANTONIO APP CON D-ATIS SAN ANTONIO TOWER GND CON CLNC DEL **CPDLC** 118,9 125.1 307.0 119.8 257.8 121.9 348.6 126.7 NM 30 4100 1849 ^ NM 20 1648 (NOPT) 2007 (IF/IAF) NATBA 3500 WATBA ¹⁸⁰⁴∧ WATBA (FAF) 1605 **EMLIW** WATBA 1101**^** ZIPEL 20 2.2 NM to RW22 3 3500 989 WATBA 1140_^ Λ²⁰⁴⁹ ۸₁₀₂₈ 1327 ^ 4100 WATBA 1098 **∧**₁₀₉₈ **IMIKE** MISSED APCH FIX ∧¹³⁷⁹ **EMBOW** 150 809 **TDZE** 770 **ELEV** D 4 NM 3100 IMIKE **EMBOW** VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 85). 4 NM 137° Λ 217° to Holding Pattern **RW22 EMLIW** *LNAV only. ZIPEL 2.2 NM to 2600 RW22 *1.3 NM to RW22 RW22 2600 GP 3.00° 1500* TCH 55 TWR 1.3 NM 0.9 NM -3.4 NM 7 NM 1030 CATEGORY LPV DA 970-3/4 200 (200-3/4) LNAV DA 1225-15/8 455 (500-1%) VNAV TDZ/CL Rwy 13R 1240-1 470 (500-1) 1240-1% 470 (500-1%) LNAV MDA REIL Rwys 13L, 22 and 31R HIRL Rwys 4-22 and 13R-31L 1300-1 1400-1 1420-13/4

MIRL Rwy 13L-31R SAN ANTONIO, TEXAS Amdt 2C 04NOV21

SAN ANTONIO INTL (SAT)

1520-21/4

711 (800-21/4)

491 (500-1)

591 (600-1)

CIRCLING

611 (700-13/4)