

APP CRS	Rwy Idg	10553
123°	TDZE	540
	Apt Elev	618

RNAV (RNP) Z RWY 12R

ST LOUIS LAMBERT INTL (STL)

For uncompensated Baro-VNAV systems, procedure NA below -16°C (4°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized with Rwy 11 except for arrivals at RRIIP and HRBEE. Use of FD or AP required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 5000 on track 123° to FONTI and hold, continue climb-in-hold to 5000.

D-ATIS	ST. LOUIS APP CON	ST. LOUIS TOWER	GND CON	CINC DEL	CPDLC
125.025	132.125 360.6	118.5 257.7	121.9 348.6 (Inbound)	119.5 363.1	
379.925			121.65 377.175 (Outbound)		
			118.925 227.125 (Rwy 11/29)		

ELEV 618 **D** TDZE 540

Rwy 6-24 7603 X 150

Rwy 11-29 9000 X 150

Rwy 12L-30R 9013 X 150

Rwy 12R-30L 11020 X 200

HIRL all Rwys
TDZ/CL Rwys 11, 12L, 12R, 29, and 30R

HOPWD

See planview for multiple IF locations.

5000 FONTI

↑
tr 123°

1700

1700

123°

RW12R

GP 3.00°

TCH 54

3.5 NM

CATEGORY	A	B	C	D
RNP 0.30 DA	998/60 458 (400-1¼)			

AUTHORIZATION REQUIRED

ST. LOUIS, MISSOURI

Orig-C 29MAR18

38°45'N-90°22'W

ST LOUIS LAMBERT INTL (STL)

RNAV (RNP) Z RWY 12R