

WAAS CH <b>86905</b> <b>W04A</b>	APP CRS <b>040°</b>	Rwy Idg <b>4775</b> TDZE <b>58</b> Apt Elev <b>72</b>
--	------------------------	---

# RNAV (GPS) RWY 4

RNP APCH - GPS.

**T** When local altimeter setting not received, use Cambridge altimeter setting; increase LPV DA to 303 feet, LNAV/VNAV DA to 670 feet and visibility  $\frac{1}{8}$  SM; increase all MDAs 60 feet and visibility  $\frac{1}{8}$  SM. **A** LNAV Cat C/D and Circling Cat C  $\frac{1}{8}$  SM, and Circling Cat D  $\frac{1}{4}$  SM. VDP and Baro-VNAV NA when using Cambridge altimeter setting. Circling Rwy 15, 33 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

**MISSED APPROACH:**  
Climb to 700 then  
climbing right turn to  
2000 direct ORETE  
and hold.

ATIS <b>124.475</b>	POTOMAC APP CON <b>133.75 254.35</b>	EASTON TOWER ★ <b>118.525 (CTAF) 0</b>	GND CON <b>119.075</b>	CLNC DEL <b>119.075</b>
------------------------	---	---	---------------------------	----------------------------