



WAAS CH <b>56499</b> <b>W20A</b>	APP CRS <b>196°</b>	Rwy Idg TDZE Apt Elev	<b>6350</b> <b>705</b> <b>705</b>	RNAV (GPS) RWY 20	
				CONCORD-PADGETT RGNL (JQF)	

RNP APCH.				MALSR		MISSED APPROACH: Climb to 3000 direct WEGTI and on track 127° to LOCAS and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV visibility all Cats to 1½ SM.						
ATIS ★	CHARLOTTE APP CON	CONCORD TOWER ★	GND CON	CLNC DEL	CLNC DEL	UNICOM
133.675	128.325 307.8	134.65 (CTAF) 0	121.85	118.55	127.25 (when twr closed)	122.95



ELEV 705

D

TDZE 705

3000

WEGTI

LOCAS

\*LNAV only.

1.8 NM to RWY 20

2400

196°

3000

GP 3.00° TCH 44

CATEGORY	A	B	C	D
LPV DA	955-1½ 250 (300-1½)			
LNAV/VNAV DA	1222-1¼ 517 (600-1¼)			
LNAV MDA	1300-1½	595 (600-1½)	1300-1¼	595 (600-1¼)
CIRCLING	1300-1	595 (600-1)	1480-2¼ 775 (800-2¼)	1480-2½ 775 (800-2½)