FORT WAYNE, INDIANA AL-157 (FAA) 23054 WAAS RNAV (GPS) RWY 31 2821 Rwy Idg TDZE APP CRS CH 77638 836 313° SMITH FLD (SMD) Apt Elev 836 W31A V Rwy 31 helicopter visibility reduction below 1 SM NA. DME/DME RNP-0.3 NA. MISSED APPROACH: Climb to Procedure NA at night. When local altimeter setting not received, use **A** NA 2700 direct GRUSS and on Fort Wayne Intl altimeter setting and increase all MDA 40 feet, LP Cat C visibility ½ SM and LNAV Cat C visibility ½ SM. track 273° to WERBU and hold. UNICOM AWOS-3 FORT WAYNE APP CON 124,55 127.2 284.6 122.8 (CTAF) (NSA RW31 25 NA MISSED APCH FIX WERBU , 2700 **(** Λ 1257 273° (12.1)**GRUSS** ^869± Procedure NA for arrivals at TWERP on V8 eastbound and V422 eastbound. 1057 🔨 YIPLU (IAF) 2 NM to RW31 **TWERP** 1648 ∧ 2600 NOP 1214 (FAF **OPOBY** 4 NM (IF/IAF) FORT WAYNE 2600 KOKTE **FWA** 081° (11.11) Procedure NA for arrival on FWA VORTAC airway radials 022 CW 174. TDZE **ELEV** 836 836 (IAF) **OSBER** 2700 GRUSS Visual Segment - Obstacles. WERBU 4 NM 273° Δ **OPOBY KOKTE** Holding Pattern YIPLU 2 NM to RW31 2600 RW31 1500 2 NM 3.3 NM 6.1 NM

FORT WAYNE, INDIANA Amdt 1A 25MAY17

MIRL Rwys 5-23 and 13-31

13 JUL 2023 to 10 AUG 2023

SMITH FLD (SMD)

1240-11/8

404 (500-11/8) 1260-11/4

424 (500-11/4) 1940-3

1104 (1200-3)

D

NA

NA

1240-1 404 (500-1)

1260-1 424 (500-1)

1400-1 564 (600-1)

CATEGORY

LNAV MDA

C CIRCLING

LP MDA

313°