

WAAS CH 40324 W19A	APP CRS 193°	Rwy Idg TDZE 804 Apt Elev 817
--	------------------------	---

RNAV (GPS) RWY 19



DOUGLAS HUNTER FLD (1M5)



RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using Bowling Green altimeter setting. When local altimeter setting not received, use Bowling Green altimeter setting and increase LPV DA to 1144 and all visibilities ¼ mile; increase all LNAV/VNAV DA to 1184 and all visibilities ¼ mile; increase all MDA 100 feet and increase LNAV Cat C/D visibility ⅜ mile.

MISSED APPROACH: Climb to 3000
direct COLBU and hold.

AWOS-3PT 118.175	NASHVILLE APP CON 119.35 372.0	UNICOM 122.975 (CTAF) 0
----------------------------	--	-----------------------------------



3000 ↑		COLBU 		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 21).			4 NM Holding Pattern				
*LNAV only.								3000		GP 3.00° TCH 40	
CATEGORY		A		B		C		D			
LPV DA		1054-1 250 (300-1)									
LNAV/ VNAV DA		1094-1½ 290 (300-1½)									
LNAV MDA		1160-1 356 (400-1)									