





APP CRS	Rwy Idg	12003
216°	TDZE	637
	Apt Elev	645

RNAV (RNP) X RWY 22L
DETROIT METRO WAYNE COUNTY (DTW)

RNP AR APCH.		MALSR	MISSED APPROACH: Climb to 4000 direct HWLER and hold.	
For uncompensated Baro-VNAV systems, procedure NA below -10°C (14°F) or above 54°C (130°F). Simultaneous approach authorized. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 4500 and RNP 0.30 all Cats visibility to RVR 6000.				
D-ATIS	DETROIT APP CON	METRO TOWER	GND CON	CLNC DEL
133.675	124.05 284.0	128.125 317.725	121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)	CPDLC



4000	↑	HWLER						DRBRN	
		HULKA	2000	ROUGE	OSKER	LUPAY	BHOLD	21°	7000
			2000	3000	4000	5000	6000		
			4.3 NM	3.3 NM	3.3 NM	3.3 NM	3.3 NM		
CATEGORY	A	B	C	D					
RNP 0.15 DA	941/24		304 (300-½)						
RNP 0.30 DA	1040/40		403 (400-¾)						
AUTHORIZATION REQUIRED									



EC-1, 13 JUL 2023 to 10 AUG 2023

EC-1, 13 JUL 2023 to 10 AUG 2023