

WAAS CH 53533 W19B	APP CRS 194°	Rwy Idg 7650 TDZE 11 Apt Elev 13
--	------------------------	---

RNAV (GPS) RWY 19R
SAN FRANCISCO INTL (SFO)



SAN FRANCISCO INTL (SFO)

RNP APCH.

▼ LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 3°C or above 42°C. Simultaneous approach authorized. Simultaneous operations require use of vertical guidance; maintain last assigned altitude until established on glidepath. Simultaneous approach NA below 28°C (52°F).

MISSED APPROACH: Climb to 600 then climbing left turn to 3000 direct KATFH and hold.

D-ATIS 113.7 115.8 118.85	NORCAL APP CON 134.5 338.2	SAN FRANCISCO TOWER 120.5 269.1	GND CON 121.8	CLNC DEL 118.2	CPDLC
---------------------------------	-------------------------------	------------------------------------	------------------	-------------------	-------



TDZ/CL Rwy's 19L and 28R
REIL Rwy's 1L, 1R and 10L
HIRL all Rwy's

600 3000 KATFH

*RNAV only.

FOBOT 3.1 NM to RW19R

ESUME 2800

HITOD 4000

194°

1100*

GP 3.15° TCH 55

1.9 NM 1.2 NM 5.1 NM 7.9 NM

CATEGORY	A	B	C	D
LPV DA		382/55 371 (400-1)		
LNAPV/VNAV DA		449-1¼ 438 (500-1¼)		
LNAPV MDA	660/55 649 (700-1)		660-1⅞ 649 (700-1⅞)	