



WAAS CH 61227 W28A	APP CRS 283°	Rwy Idg TDZE Apt Elev	4002 839 859
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 28

MID-OHIO VALLEY RGNL (PKB)

RNP APCH. <div><div>▼</div><div>▲</div></div> <div>Rwy 28 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Athens/Albany altimeter setting and increase all MDA 100 feet, increase LP/LNAV Cts C/D visibility ¼ SM and Circling Cat C/D ½ SM. Straight-in Rwy 28 NA at night, Circling Rwy 10, 28 NA at night.</div>		MISSED APPROACH: Climb to 3000 direct FASAT and hold.		
ATIS 124.35	INDIANAPOLIS CENTER 125.55 317.475	PARKERSBURG TOWER ★ 123.7 (CTAF) 257.8	GND CON 126.45	UNICOM 122.95



3000		FASAT	Visual Segment - Obstacles.		4 NM Holding Pattern	
RW28		BANLE	CAPNA		103° → 6000 ← 283° 3000	
4.7 NM		6.3 NM				
CATEGORY	A	B	C	D		
LP MDA	1300-1	461 (500-1)	1300-1½	461 (500-1½)		
LNAV MDA	1320-1	481 (500-1)	1320-1½	481 (500-1½)		
CIRCLING	1320-1 461 (500-1)	1380-1 521 (600-1)	1640-2¼ 781 (800-2¼)	1640-2½ 781 (800-2½)		