EC-2, 13 JUL 2023 to 10 AUG 2023

RNAV (GPS) RWY 1

WARREN COUNTY/JOHN LANE FLD (I68)

V A NA

130°F). Boro-VNAV and VDP NA when using Dayton/Wright Brothers altimeter setting. DME/DME RNP-0.3 NA. Rwy 1 helicopter visibility reduction below 3/4 SM NA. When local altimeter setting not received use Dayton/Wright Brothers altimeter setting and increase LPV DA to 1183 feet and LNAV/VNAV DA to 1215 and all MDA 40 feet; increase LNAV Cat C/D visibility ½ SM and Circling Cat C visibility ½ SM. When Circling to Rwy 19 at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C

MISSED APPROACH: Climb to 1400 then climbing left turn to 3000 direct ELIHO and hold.

COLUMBUS APP CON AWOS-3 CLNC DEL UNICOM 120.55 123.075 (CTAF) 0 118.85 269.275 119,4 ۸¹⁴⁰² MISSED APCH FIX Procedure NA for arrivals at MIZZA on V47 northbound. MIZZA 1136 1009± ^ 1329 1121 (FAF) ZÁMHO Λ¹⁵⁶⁸ SARW01 25 Ny 3100 NoPT for arrival at WUSPU (IF/IAF) **(** on V5 northeast bound WUSPU Δ1849 893 **ELEV 898 TDZE** MIRL Rwy 1-19 0 VGSI and RNAV glidepath not coincident ЕЦНО 4 NM 1400 3000 REIL Rwys 1 and 19 (Holding Pattern (VGŠI Angle 3.20/TCH 33). WUSPU 61 Δ 2800 *LNAV only ZAMHO 2500 *1.1 NM RW01 GP 3.20° 2500 TCH 60 7 6 NM 3.5 NM CATEGORY D LPV 1157-1 264 (300-1) NA LNAV/ DA 1189-1 296 (300-1) NA VNAV LNAV MDA 1260-1 367 (400-1) - 009° 1400-1 1480-1 1480-2 1480-11/2 **CIRCLING** 502 (600-1) 582 (600-1) 582 (600-11/2) 582 (600-2)

LEBANON, OHIO Amdt 3 05JAN17 WARREN COUNTY/JOHN LANE FLD (168)