WAAS	APP CRS	Rwy Idg	4403
CH 69531	276°	TDZE	2036
W27A		Apt Elev	2037

RNAV (GPS) RWY 27

POPLAR MUNI (P01)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP -0.3 NA. When local altimeter setting not received, use Wolf Point altimeter setting: increase LPV DA to 2332, LNAV/VNAV DA to 2582 and all Cats visibility ⅛ SM; increase all MDAs 60 feet and Circling Cat C/D visibility ¼ SM. Baro-VNAV and VDP NA with Wolf Point altimeter setting. Helicopter visibility reduction below 1 SM not authorized. Circling NA to Rwy 2/20.

MISSED APPROACH: Climb to 6000 direct ORMOW and on track 246° to DORIA and hold, continue climb-in-hold to 6000.

AWOS-3PT	SALT LAKE CITY CENTER	UNICOM
135.325	126.85 305.2	122.8 (CTAF) L



ELEV 2037 TDZE 2036





CATEGORY	A	B	C	D
LPV DA	2286-1 250 (300-1)			
LNAV/VNAV DA	2536-1¾ 500 (500-1¾)			
LNAV MDA	2480-1 444 (500-1)		2480-1⅜ 444 (500-1⅜)	
CIRCLING	2560-1 523 (600-1)	2600-1 563 (600-1)	2600-1½ 563 (600-1½)	2740-2¼ 703 (800-2¼)

MIRL Rwy 9-27 L

NW-1, 13 JUL 2023 to 10 AUG 2023
NW-1, 13 JUL 2023 to 10 AUG 2023