

WAAS CH <b>57917</b> <b>W01A</b>	APP CRS <b>008°</b>	Rwy Idg <b>5000</b> TDZE <b>969</b> Apt Elev <b>969</b>
--	------------------------	---

RNAV (GPS) RWY 1  
LAFAYETTE MUNI (3M7)

RNP APCH - GPS.



▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. Obtain local altimeter setting on CTAF; when not received, use Bowling Green altimeter setting: increase LPV DA to 1441 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 1585 feet and all visibilities ½ SM; increase all MDAs 140 feet and visibility LNAV Cat C and D ¼ SM and Circling Cat C and D ½ SM. VDP and Baro-VNAV NA when using Bowling Green altimeter setting. Rwy 1 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:  
Climb to 3000 direct  
OZESI and hold.

NASHVILLE APP CON <b>118.4 360.7</b>	UNICOM <b>122.8 (CTAF) 0</b>
---	---------------------------------



SE-1, 13 JUL 2023 to 10 AUG 2023

SE-1, 13 JUL 2023 to 10 AUG 2023