10 AUG 2023

2

13 JUL 2023

10201 WAAS Rwy Idg APP CRS CH 62911 1380 TDŻE 303° Apt Elev 1384 **W30A** 

## RNAV (GPS) Y RWY 30C PHOENIX-MESA GATEWAY (IWA)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -2°C (29°F) or above 35°C (95°F). DME/DME RNP- 0.3 NA. When local altimeter setting not received, use Phoenix Sky Harbor Intl altimeter setting and increase LPV DA to 1660 feet, LNAV/VNAV DA to 1710 feet and all MDA 80 feet; increase LPV all Cats visibility 1/8 SM, increase LNAV/VNAV all Cats, LNAV Cats C, D and E, and Circling Cats D, E visibility 1/4 SM. VDP and Baro-VNAV NA with Phoenix Sky Harbor Intl altimeter setting


MISSED APPROACH: Climb to 2800 then climbing left turn to 5000 direct GICGE and hold

ATIS \* 133.5 270.275

PHOENIX APP CON 124.9 353.8

GATEWAY TOWER ★ 120.6 (CTAF) 289.4

GND CON 128.25 275.8 CLNC DEL



., RW30C 3000 GP 3.00° 2020\* TCH 42 1.2 NM 0.7 3.1 NM A NM CATEGORY 1580-3/4 200 (200-3/4) LPV LNAV/ 1630-7/8 250 (300-7/8) DA VNAV 1800-11/8 420 (500-11/8) LNAV MDA 1800-1 420 (500-1) 1880-11/2 2000-2 2040-21/4 CIRCLING 1880-1 496 (500-1) 496 (500-1½) 616 (700-2) 656 (700-21/4)

1496 303°

MIRL Rwy 12R-30L HIRL Rwys 12L-30R and 12C-30C REIL Rwys 12L and 30R

PHOENIX, ARIZONA Amdt 1C 12AUG21