NC-3,

13 JUL 2023 to 10 AUG 2023

APP CRS Rwy Idg 5000 179° TDZE 1316 Apt Elev 1321

RNAV (GPS) RWY 18

FLOYD W JONES LEBANON (LBO) 1321 When local altimeter setting not received, use Springfield-Branson Ntl altimeter setting: V MISSED APPROACH: Climb to increase LNAV/VNAV DA to 2043 feet; increase all MDAs 120 feet and Circling 3500 direct KUPIW and hold. 🛦 NA visibility Cat C/D ½ SM. Baro-VNAV NA when using Springfield-Branson Ntl altimeter setting. Baro-VNAV NA below -17° C (1° F). DME/DME RNP-0.3 NA. AWOS-3PT SPRINGFIELD APP CON CLNC DEL UNICOM 118.975 121.1 290.5 123,725 122,8 (CTAF) (30 MM to WIKGI (Nop) 4 NM 3500 (IF/IAF) WIKGI . WIKGI 089 (IAF) 269 UTMIH 3500 NoPT 3500 NoPT 089 269 (IAF) 2083 (5) (5) TIHCY (FAF) 269° UTMIH 1759 ULIKY TIHCY NA TO UTMIH 3500 1611**/**. ۸₁₆₂₂ 3500 14 NIM to THE 1453**A** 1365 RW18 1456 4 NM 1755 ^ ELEV 1321 TDZE 1316 KUPIW

179° VGSI and descent angles not coincident (VGSI Angle 3.00/ TCH 40) **KUPIW** 81 3500 3% UP *LNAV only, VDP NA when using (F) 4 NM Springfield-Branson Ntl altimeter Holding Pattern setting ULIKY *1.3 NM to 3500 RW18 5000 X 75 **RW18** 2700 GP 3.00° TCH 40 1.3 2.9 NM 5.8 NM CATEGORY С D GLS PA DA NA LNAV/ DA 1937-2 1/4 621 (700-21/4) VNAV LNAV MDA 1760-11/4 1760-1 444 (500-1) 444 (500-11/4)

MIRL Rwy 18-36 (LEBANON, MISSOURI Orig-C 16JUN22

REIL Rwys 18 and 36 1

FLOYD W JONES LEBANON (LBO) RNAV (GPS) RWY 18

1980-2

659 (700-2)

1980-13/4

659 (700-13/4)

1820-1

499 (500-1)

CIRCLING

1860-1

539 (600-1)