ALICEVILLE, ALABAMA AL-9812 (FAA) 21280 RNAV (GPS) RWY 24 Rwy Idg TDZE 5001 APP CRS 150 244° GEORGE DOWNER (AIV) Apt Elev 150 DME/DME RNP-0.3 NA. Use Tuscaloosa altimeter setting; when not received, use V MISSED APPROACH: Columbus/W Point/Starkville altimeter setting and increase all MDAs 20 feet, and **A** NA Climb to 3000 direct Circling Cat C visibility ¼ SM. Procedure NA at night. Rwy 24 helicopter visibility ZESLO and hold. reduction below 1 SM NA. TCL ASOS COLUMBUS APP CON UNICOM 132,825 135.6 323.275 122.8 (CTAF) (4 NM 1314 2000 (IF/IAF) ⁵¹⁵∧ CÍKOB 8 **CIKOB** 3000 ZOLUĞ 704 MERIDIAN 1 **FFPON WEST MOA** 2.8 NM to RW24 **ZESLO** 30 MERIDIAN 1 EAST MOA 3000

CIKOB Holding Pattern **ZOLUG FEPON** 3000 2.8 NM to RW24 RW24 2000 1100 2.8 NM--2.8 NM-6.4 NM-С D CATEGORY 740-13/4 LNAV MDA 740-1 590 (600-13/4) 590 (600-1) MIRL Rwy 6-24 **(** 820-13/4 900-21/2 **C** CIRCLING 740-1 590 (600-1) REIL Rwys 6, 24 **Q** 670 (700-13/4) 750 (800-21/2) ALICEVILLE, ALABAMA GEORGE DOWNER (AIV)

Visual Segment - Obstacles

Orig-A 05JAN17

4 NM

150 **TDZE**

> 244° to RW24

> > 3000

ZESLO

150

SE-4,

13 JUL 2023 to

10 AUG 2023

ELEV

RNAV (GPS) RWY 24

CIKOB

4 NM

(NoP)