

RNAV (RNP) Z RWY 5R
INDIANAPOLIS INTL (IND)

MISSED APPROACH:
Climb to 1500, then climbing
right turn to 3000 direct
OZMOE and hold.

RADAR required for procedure entry at ATEEN.

(IF) ATEEN
5000 210K
(RF REQD)

3000 127° (7.3)

MSA RW05R 25 NM
3100

HORNT 200K

2100 (3.1)

BG TEN

2100 049° (2.8)

(FAF) HUUPS

2100 (5)

KYYL 200K

3600 (2.4)

JAANE

4400 230° (5.7)

(IF) KNIGT
6000 210K
(RF REQD)

RADAR required for procedure entry at KREEM.

(IF) KREEM
5000 210K
(RF REQD)

3600 284° (4.5)

Δ 1259

(IF) BIGRD

4000 049° (3.1)

(IF) IIUUU
5000 210K

MISSED APCH FIX

ELEV 796 D TDZE 791

OZMOE

140° 4 NM

320°

VGS1 and RNAV glidepath not coincident (VGS1 Angle 3.00/TCH 71).

HUUPS

2100

2100 050°

GP 3.00° TCH 50

4 NM

RW05R

1500 3000 OZMOE

See planview for multiple IF locations.

CATEGORY	A	B	C	D
RNP 0.11 DA		1174/45	383 (400-%)	
RNP 0.30 DA		1271/60	480 (500-1½)	

AUTHORIZATION REQUIRED

HIRL all Rwy's
TDZ/CL Rwy's 5L and 5R

EC-2, 13 JUL 2023 to 10 AUG 2023

EC-2, 13 JUL 2023 to 10 AUG 2023