

WAAS CH 77735 W09A	APP CRS 093°	Rwy Idg TDZE 1198 Apt Elev 1198
--	------------------------	---

RNAV (GPS) RWY 9


PORTAGE COUNTY (POV)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Akron-Canton Rgnl altimeter setting and increase all DA 50 feet and all MDA 60 feet, increase LNAV Cat C visibility ¼ mile, LNAV/VNAV all Cats and Circling Cat C visibility ¼ mile. Baro-VNAV NA with Akron-Canton Rgnl altimeter setting. Helicopter visibility reduction below 1 SM NA. Night landing Cat C: Procedure NA.

MISSED APPROACH: Climb to 4000 direct WHINR and hold.

AWOS-3 118.675	CLEVELAND APP CON★ 118.6 371.875	CLNC DEL 125.65	UNICOM 123.05 (CTAF) 📶
--------------------------	--	---------------------------	---



4 NM Holding Pattern		4000		WHINR	
GP 3.00° TCH 40		2800		RW09	
6.1 NM		4.9 NM		3499 X 75	
CATEGORY	A	B	C	D	
LPV DA	1448-1	250 (300-1)		NA	
LNAV/VNAV DA	1507-1	309 (400-1)		NA	
LNAV MDA	1760-1	562 (600-1)	1760-1½ 562 (600-1½)	NA	
CIRCLING	1760-1 562 (600-1)	1800-1 602 (700-1)	1920-2 722 (800-2)	NA	

REIL Rwy 9 and 27 **📶**
MIRL Rwy 9-27 **📶**

EC-2, 13 JUL 2023 to 10 AUG 2023

EC-2, 13 JUL 2023 to 10 AUG 2023