NW-1, 13 JUL 2023 to 10 AUG 2023

Rwy Idg TDZE Apt Elev WAAS 5005 APP CRS CH **78026** 3443 230° W23A 3443

## RNAV (GPS) RWY 23 $_{\text{SHELBY}} (\mathrm{SBX})$

DME/DME RNP-0.3 NA. use Great Falls altimeter s 100 feet; increase LPV all LNAV Cats C/D, Circling	Baro-VNAV NA. Rwy 23 helicopter visibility reduction below 1 SM NA. DME/DME RNP-0.3 NA. Use Cut Bank altimeter setting, if not received use Great Falls altimeter setting and increase all DA 81 feet and all MDA 100 feet; increase LPV all Cats visibility ¾ mile, LNAV/VNAV all Cats, LNAV Cats C/D, Circling Cats C/D visibilities ¼ mile. Straight-in Rwy 23 NA at night.			MISSED APPROACH: Climb to 4300 then climbing right turn to 9000 direct YENUP and hold, continue climb-in-hold to 9000.		
AWOS-3PT <b>128.325</b>	CTB ASOS <b>119.025</b>	SALT LAKE CI 133.4				
CUT BANK CTB > 9000 to YENUP 067° (30.8) 4368	3546A 3546A RW23 36:	ZIRTA JIKBO 1.8 NM to RW23 55	51000	(IF/IAF) YENUP	₩ 23 25 N <sub>M</sub> 8200  ©	
MIDI Prograf 22 and 11 29	*LNAV only.  *LNAV only.  1  RW23  -1.8 NM  CATEGORY  LPV DA  LNAV/ DA  LNAV/ DA  LNAV MDA	NUP VGSI and RNA (VGSI Angle 3.)  ZIRTA	00/TCH 32).  00  230°  5100  7.5 NM  B  13-1½  370  0-1)  80-1	YENUP  0.5  0.6  0.1400-11/6)  0.1400-13/8  4100-13/4	4220-21/2	
MIRL Rwys 5-23 and 11-29 🚺				57 (700-1¾)	777 (800-2½)	

SHELBY, MONTANA Amdt 2B 02MAR17