


WAAS CH 40113 W08B	APP CRS 087°	Rwy Idg 10001 TDZE 794 Apt Elev 794
----------------------------------------	------------------------	----------------------------------------------------------------

RNAV (GPS) RWY 8R

GERALD R FORD INTL (G.R.R.)

RNP APCH.			MALSR		MISSED APPROACH: Climb to 2700 direct CAVUS and on track 085° to SARAN and hold.	
ASR For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. For inop ALS, increase LNAV Cat D visibility to RVR 6000. ** RVR 1800 authorized with use of FD or AP or HUD to DA.						
ATIS 118.725	GREAT LAKES APP CON ★ 128.4 257.6	GRAND RAPIDS TOWER★ 135.65 (CTAF) 339.8	GND CON 121.8	CLNC DEL 119.3	UNICOM 122.95	



GP 3.00° TCH 51						
7.7 NM 2.3 NM 1.4 NM 1.1 NM						
CATEGORY	A			B	C	D
LPV DA **	994/24			200 (200-½)		
LNAV/ VNAV DA	1297/50			503 (600-1)		
LNAV MDA	1180/24 386 (400-½)			1180/35 386 (400-¾)		1180/50 386 (400-1)
C CIRCLING	1260-1 466 (500-1)			1340-1½ 546 (600-1½)		1360-2 566 (600-2)

