RNAV (GPS) Y RWY 23L
RALEIGH-DURHAM INTL (RDU)

WAAS CH 65713 W23B	APP CRS 234°	Rwy ldg 7500 TDZE 435 Apt Elev 435

RNP APCH-GPS.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV Cat C/D visibility to 1⅜ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 2600 direct ZEBUL and hold.

D-ATIS	RALEIGH APP CON	RALEIGH TOWER (EAST)	RALEIGH TOWER (WEST)	GND CON (EAST)	GND CON (WEST)	CLNC DEL	CPDLC
123.8	127.675 307.9	127.45 257.8 Rwys 5R-23L and 14-32	119.3 257.8 Rwy 5L-23R	121.9 348.6 Rwys 5R-23L and 14-32	121.7 348.6 Rwy 5L-23R	120.1	



ELEV 435 | D | TDZE 435





REIL Rwy 32
MIRL Rwy 14-32
HIRL Rwys 5R-23L and 5L-23R
TDZ/CL Rwys 5L, 23R, and 23L

CATEGORY		A	B	C	D
LPV	DA	635/18 200 (200-½)			
LNAV/VNAV	DA	820/35 385 (400-⅝)			
LNAV	MDA	920/24 485 (500-½)		920/50 485 (500-1)	
C CIRCLING		960-1 525 (600-1)		1020-1½ 585 (600-1½)	1180-2½ 745 (800-2½)

SE-2, 13 JUL 2023 to 10 AUG 2023
SE-2, 13 JUL 2023 to 10 AUG 2023