RICE LAKE, WISCONSIN 23110 AL-9210 (FAA) RNAV (GPS) RWY 1 6500 WAAS Rwy Idg APP CRS CH 86217 1101 TDZE 010° RICE LAKE RGNL/CARL'S FLD (RPD) Apt Elev 1109 W01A If local altimeter setting not received, use Chippewa Valley Rgnl altimeter setting and increase all DAs/MDAs 120 feet. DME/DME RNP-0.3 NA. Baro-VNAV NA V MISSED APPROACH: MALSR A below -17°C (3°F). Baro VNAV and VDP NA when using Chippewa Valley Rgnl Climb to 3200 direct altimeter setting. For inoperative MALSR, increase LPV visibility to 1, and LNAV ORBEW and hold. Cat D visibility to 11/4. Circling Rwy 13, 31 NA at night. AWOS-3 MINNEAPOLIS CENTER UNICOM 120.525 125.3 335.6 122.7 (CTAF) ( **ALEEN** 2002 4 NM ORBE\ Λ 1385 <sup>1634</sup>∧ 1148 **1**339 169± **JADIX** 1737± **∧** 1.9 NM to RW01 RW01 25 N (FAF) KOHHL 3200 (IAF) 3200 NoP CENOS  $\Diamond$ 3200 Procedure NA for arrival at 077° (30.2) EAU VORTAC on airway radials 265 CW 357. (IF/IAÉ) HÉRRB STILS TDZE 1101 **ELEV 1109** REIL Rwys 13, 31 (IAF) REIL Rwy 19 🌘 EAU CLAIRE HIRL Rwy 1-19 ( **EAU** MIRL Rwy 13-31 ORBEW VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 28). 3200 4 NM Holding Pattern **HERRB** KOHHL JADIX 1.9 NM to \* LNAV only 3200 **RW01** \*1.3 NM to RW01 GP 3.00° 3100 TCH 45 1760 6 NM 4.2 NM CATEGORY IPV 1390-1/2 289 (300-1/2) DA LNAV/ DA 1440-3/4 339 (400-3/4) VNAV 1520-3/4 1520 - 1LNAV MDA 1520-1/2 419 (500-1/2) 010° 419 (500-34) 419 (500-1) 1740-11/4 1940-23/4 1600-11/4 1740-13/4 **C** CIRCLING 493 (500-11/4) 631 (700-11/4) 631 (700-1¾ 831 (900-23/2

RICE LAKE, WISCONSIN Amdt 1A 02JAN20 rice lake rgnl/carl's fld (RPD)

RNAV (GPS) RWY 1

EC-3, 13 JUL 2023 to 10 AUG 2023