V

NC-1, 13 JUL 2023 to 10 AUG 2023

RNAV (GPS) RWY 32 BENSON MUNI (BBB)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below-17°C or above 54°C . Rwy 32 helicopter visibility reduction below $^3\!\!/4$ SM NA. Baro-VNAV NA when using Appleton altimeter setting. When local altimeter setting not received, use Appleton altimeter setting and increase all DA and MDA 40 feet.

MISSED APPROACH: Climb to 2700

A direct DOSCA and hold. AWOS-3 MINNEAPOUS CENTER UNICOM 118,45 125.5 323.1 122.8 (CTAF) (MISSED APCH FIX ARMUW Procedure NA for arrivals at ARMUW via V175 northbound. **1576 1 ॐ∧** 1332 RW32 (FAF) CUCAT (IAF) GOREC RW32 25 Ny 3400 **(** (IAF) HAXU FETUD **ELEV 1039** TDZE 1039 (IAF) CLAPS ARDUE 2700 DOSCA **FETUD** 4 NM Holding Pattern CUCAT **RW32** GP 3.00° 2600 TCH 41 4.7 NM 6.3 NM CATEGORY D LPV DA 1426-11/2 387 (400-11/2) NA 319 LNAV/ DA NA 1710-21/2 671 (700-21/2) VNAV MIRL Rwy 14-32 LNAV MDA 1700-1 661 (700-1) NA REIL Rwys 14 and 32 0

BENSON, MINNESOTA Amdt 1A 18JUL19

BENSON MUNI (BBB) RNAV (GPS) RWY 32