


APP CRS	Rwy ldg	10526
259°	TDZE	2069
	Apt Elev	2181

RNAV (RNP) RWY 26L
HARRY REID INTL (LAS)

RNP AR APCH.		MALSF	MISSED APPROACH: Climb to 7000 on the RNAV missed approach route to BLD VORTAC and hold. *Missed approach requires minimum climb of 255 feet per NM to 3200.	
▼ For uncompensated Baro-VNAV systems, procedure NA below 0°C or above 54°C.				
D-ATIS	LAS VEGAS APP CON	LAS VEGAS TOWER	GND CON	CLNC DEL
132.4	125.025 379.15 (West) 119.775 282.2 (East)	118.75 257.8 (Rwy 1L/19R, 1R/19L) 119.9 257.8 (Rwy 8L/26R, 8R/26L)	121.1 270.8 E of 1R/19L 121.9 254.3 W of 1R/19L	118.0
				CPDLC



ELEV 2181

TDZE 2069

MIRL Rwy 1R-19L
REIL Rwy 1R, 8R, 19L and 19R
HIRL Rwy 1L-19R, 8L-26R and 8R-26L

7000	KACEK	RUDYY	SELLZ	TTONE	BLD
↑ tr 259°	✧ tr 255°	✧ tr 189°	✧ tr 127°	✧ tr 063°	◻
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 84).					
See planview for multiple IF locations.					
CATEGORY	A	B	C	D	
RNP 0.30 DA*	2450-7/8 381 (300-7/8)				
RNP 0.30 DA	2502-1 433 (400-1)				
AUTHORIZATION REQUIRED					

SW-4, 13 JUL 2023 to 10 AUG 2023

SW-4, 13 JUL 2023 to 10 AUG 2023