
SC-1, 13 JUL 2023 to 10 AUG 2023

TEXARKANA, ARKANSAS AL-420 (FAA) 22363 WAAS 6601 RNAV (GPS) RWY 22 Rwy Idg APP CRS Ch 53699 TDŹE 384 220° TEXARKANA RGNL-WEBB FLD (TXK)390 **W22A** Apt Elev DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV MALSR NA below -15°C (5°F) or above 48°C (118°F). When local altimeter setting not received, MISSED APPROACH: A use J Lynn Helms Sevier County altimeter setting and increase all DA/MDA 100 feet, Climb to 2000 direct increase LPV all Cats visibility ¼ mile, LNAV/VNAV all Cats visibility ½ mile, LNAV and YOBUG and hold. circling Cat C and D visibility 1/4 mile. Baro-VNAV and VDP NA when using J Lynn Helms Sevier County altimeter setting. For inoperative MALSR when using J Lynn Helms Sevier County altimeter setting increase LPV all Cats visibility to 1½. FORT WORTH CENTER TEXARKANA TOWER★ GND CON 120.2 123.925 269.475 123.875 (CTAF) 0 235.625 119.225 (IAF) TÒYÓY Λ⁹⁴⁵ (IF) WORPA Procedure NA for arrivals at WEEBR via V278 eastbound. (FAF) (IAF) VEEBR RW22 25 NZ 505 2000 809 ۸⁶⁵¹ ۸⁶⁸⁹ \bigcirc

YOBUG 2000 YOBUG Procedure Turn CUDPA WORPA NA * LNAV only. **-**220° 2100 *1.2 NM to RW22 2100 RW22 GP 3.00° TCH 45 4 NM 7.3 NM CATEGORY D 634-1/2 LPV 250 (300-1/2) LNAV/ 687-3/4 DA 687-1/2 303 (300-1/2) VNAV 303 (300-3/4) 820-3/4 820-1 LNAV MDA 820-1/2 436 (500-1/2) 436 (500-3/4) 436 (500-1) 820-1 900-1 1000-13/4 1080-21/4 CIRCLING

510 (600-1)



TDZE 384

TEXARKANA, ARKANSAS Orig-B 02DEC21

430 (500-1)

MISSED APCH FIX

TEXARKANA RGNL-WEBB FLD (TXK) RNAV (GPS) RWY 22

HIRL Rwy 4-22 0

390

690 (700-21/4)

610 (700-134)