



WAAS CH 86812 W24A	APP CRS 245°	Rwy Idg TDZE Apt Elev	7500 730 732
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24
ERIE INTL/TOM RIDGE FLD (ERI)

RNP APCH - GPS.	MALSR 	MISSED APPROACH: Climb to 3000 direct LADVE and hold.
<p> Circling to Rwy 2 and 20 NA at night. Circling NA southeast of Rwy 6-24. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS increase LNAV/VNAV all Cats visibility to RVR 6000.</p>		

ATIS 120.35	BUFFALO APP CON ★ 121.0 257.8	ERIE TOWER ★ 118.1 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 126.8	UNICOM 122.95
-----------------------	---	---	-------------------------	--------------------------	-------------------------



ELEV 732	TDZE 730
HIRL Rwy 6-24 0 MIRL Rwy 2-20 0	

CATEGORY	A	B	C	D
LPV DA	942/24 212 (300-½)			
LNAV/VNAV DA	1146/40 416 (500-¾)			
LNAV MDA	1160/24 430 (500-½)	1160/40 430 (500-¾)		
CIRCLING	1160-1 428 (500-1)	1200-1 468 (500-1)	1200-1½ 468 (500-1½)	1340-2 608 (700-2)