

WAAS
CH **56412**
W17A

APP CRS
174°

Rwy Idg
TDZE
Apt Elev

6500
845
846

RNAV (GPS) RWY 17

MONROE COUNTY (BMG)

RNP APCH.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F). Rwy 17 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Terre Haute Rgnl altimeter setting and increase all DA 121 feet and all MDA 140 feet. Increase LPV all Cats, LNAV/VNAV all Cats, LNAV Cat C/D visibility ½ mile.

MISSED APPROACH: Climb to 3000 direct ALFRD and hold.

ASOS 134.525	HULMAN APP CON 128.025 339.8	BLOOMINGTON TOWER ★ 120.775 (CTAF) 0	GND CON 121.9	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------

4 NM

174°

354°

(IF/IAF) ITYEF

(IAF) EDISY

3000 NoPT (5)

264° (5)

3000 272° (13.2)

MOUTH

(IAF) ZESXY

084° (5)

2500 174° (6.5)

(FAF) OGUSY

3000 to ITYEF 353° (12.4)

1098

1199

1339

1096±

1092

982±

1044

HOOSIER OOM

Procedure NA for arrivals at OOM VORTAC via V303 southwest bound.

BUNKA

3000 052° (23.8)

MISSED APCH FIX

ALFRD

174°

354°

4 NM

MSA RW 17 2.5 NM

3100

1452

4 NM Holding Pattern

ITYEF

OGUSY

RW17

3000

174°

354°

2500

6.5 NM

3.2 NM

1.8 NM

GP 3.00° TCH 40

3000

ALFRD

*LNAV only

*1.8 NM to RW17

CATEGORY	A	B	C	D
LPV DA	1229-1¼ 384 (400-1¼)			
LNAV/VNAV DA	1404-2 559 (600-2)			
LNAV MDA	1460-1 614 (700-1)	1460-1¾ 614 (700-1¾)	1460-2 614 (700-2)	

ELEV 846

TDZE 845

174° to RW17

L1

4

6500 X 150

913

917

3798 X 100

35

MIRL Rwy 6-24 0

HIRL Rwy 17-35 0

REIL Rwy 17

BLOOMINGTON, INDIANA

Amdt 1C 18JUL19

MONROE COUNTY (BMG)

RNAV (GPS) RWY 17

39°09'N-86°37'W