

WAA5	APP CRS	Rwy ldg	3700
CH 69536	218°	TDZE	354
W22A		Apt Elev	354

RNAV (GPS) RWY 22


WASILLA (IYS) (PAWS)

RNP APCH.

⚠ Circling NA to Rwy 4S and 22S. Baro-VNAV and VDP NA when using Palmer altimeter setting. Rwy 22 helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. When local altimeter setting not received, use Palmer altimeter setting and increase all DA 46 feet, MDA 60 feet and all visibilities 1/8 mile.

MISSED APPROACH:
Climb to 1000 then
climbing right turn to
3000 direct BGQ
VORTAC and hold.

AWOS-3P	ANCHORAGE APP CON	CTAF
135.25	119.1 363.2	122.8 0



ELEV 354	TDZE 354
----------	----------

218° to RW22

0.4% UP - 1690 X 60'

0.5% UP - 3700 X 75'

1000	3000	BGQ
*LNAV only	ODUWU 1.9 NM to RW22	WOKNA 2500
	*1.2 NM to RW22	
	1060*	
	1.2 NM	0.7 NM
	4.1 NM	6 NM

JODBI 4400

227°

2500

GP 3.31°

TCH 40

CATEGORY	A	B	C	D
LPV DA	604-3/4	250 (300-3/4)	NA	
LNAV/VNAV DA	821-1 1/2	467 (500-1 1/2)	NA	
LNAV MDA	800-1	446 (500-1)	NA	
CIRCLING	1000-1	646 (700-1)	NA	

AK, 15 JUN 2023 to 10 AUG 2023

AK, 15 JUN 2023 to 10 AUG 2023