

WAAS
CH **50343**
W22A

APP CRS
220°

Rwy Idg
TDZE
Apt Elev

5000
5577
5589

RNAV (GPS) RWY 22
HUNT FLD (LND)

▼

⚠

Circling NA southeast of Rwy 4 and 22. Circling Rwy 4 NA at night. Rwy 22 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -26°C or above 54°C.

MISSED APPROACH: (Do not exceed 165K until R/W VOR/DME) Climb to 6280 then climbing right turn to 8200 direct R/W VOR/DME and hold.
#Missed approach requires minimum climb of 355 feet per NM to 6700.

ASOS 118.15	SALT LAKE CENTER 133.25 285.6	UNICOM 122.8 (CTAF) 0
-----------------------	---	---------------------------------

Procedure NA for arrival on R/W VOR/DME
airway radials 113 CW 170.

Key features of the chart:

- IAF RIVERTON:** 8100 NoPT (19.3) 7 NM, 113° radial, 293° bearing.
- CIKUV (IF/IAF):** 7200 (15) 220° bearing, 7 NM from RIVERTON.
- ZEMTO (FAF):** 5811, 7200 (15) 220° bearing, 7 NM from CIKUV.
- CUDKI:** 8100 (17) 342° bearing, 7 NM from ZEMTO.
- JIVOL:** 8100 280° (11.6) bearing, 7 NM from CUDKI.
- WORBA (IAF):** 8900 NoPT (29.7) 281° bearing, 7 NM from JIVOL.
- MSA RW22 2.5 NM:** 14400.
- 7 NM Holding Pattern:** 8800/8100, 040°/220°.
- GP 3.00° TCH 41.**

ELEV 5589	TDZE 5577																														
<div><div><div>220° to RW22</div><div>0.6% UP</div><div>5000 X 75</div></div></div>																															
<div><div><div>6280 8200 RW</div><div>*LNAV only</div><div>*2.9 NM to RW22</div><div>7200 7200</div><div>7 NM Holding Pattern</div><div>040° 8800 220° 8100</div><div>GP 3.00° TCH 41</div></div></div>																															
<table><tr><th>CATEGORY</th><th>A</th><th>B</th><th>C</th><th>D</th></tr><tr><td>LPV DA#</td><td>5827-¾</td><td>250 (300-¾)</td><td></td><td>NA</td></tr><tr><td>LPV DA</td><td>6060-1⅓</td><td>483 (500-1⅓)</td><td></td><td>NA</td></tr><tr><td>LNAV/VNAV DA</td><td>6040-1⅓</td><td>463 (500-1⅓)</td><td></td><td>NA</td></tr><tr><td>LNAV MDA</td><td>6460-1¼</td><td>883 (900-1¼)</td><td>6460-2½ 883 (900-2½)</td><td>NA</td></tr><tr><td>CIRCLING</td><td>6460-1¼</td><td>871 (900-1¼)</td><td>6540-3 951 (1000-3)</td><td>NA</td></tr></table>		CATEGORY	A	B	C	D	LPV DA#	5827-¾	250 (300-¾)		NA	LPV DA	6060-1⅓	483 (500-1⅓)		NA	LNAV/VNAV DA	6040-1⅓	463 (500-1⅓)		NA	LNAV MDA	6460-1¼	883 (900-1¼)	6460-2½ 883 (900-2½)	NA	CIRCLING	6460-1¼	871 (900-1¼)	6540-3 951 (1000-3)	NA
CATEGORY	A	B	C	D																											
LPV DA#	5827-¾	250 (300-¾)		NA																											
LPV DA	6060-1⅓	483 (500-1⅓)		NA																											
LNAV/VNAV DA	6040-1⅓	463 (500-1⅓)		NA																											
LNAV MDA	6460-1¼	883 (900-1¼)	6460-2½ 883 (900-2½)	NA																											
CIRCLING	6460-1¼	871 (900-1¼)	6540-3 951 (1000-3)	NA																											

LANDER, WYOMING

Orig-A 27FEB20

42°49'N-108°44'W

HUNT FLD (LND)

RNAV (GPS) RWY 22