3750 Rwy Idg APP CRS TDŹE 69 254° Apt Elev 70

¹⁰⁹⁶∧

V

Δ

RNAV (GPS) RWY 25 SUFFOLK EXEC (SFQ)

2300 7408 ORF

setting and increase all MDA 60 feet. AWOS-3 NORFOLK APP CON

DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA.

When local altimeter setting not received, use Norfolk Intl altimeter

⁵⁶⁸∧

193∧

2000

CATEGORY

LALSE

MISSED APPROACH: Climb to 2000 direct LALSE and hold.

UNICOM 119.375 122.7 (CTAF) (127.9 269.425 (IAF) **NORFOLK**

Procedure NA for arrivals on ORF VORTAC airway radials 216 CW 233. Λ¹²⁸²

ZOTID (FAF)

LALSE

4 NM

ELEV 70


NE-3, 13 JUL 2023 to 10 AUG 2023

ŴOVÍ

RW 25 25 Ny 2300 **(**

> 4 NM Holding Pattern

> > D



TDZE 69

ZOTID WOVI **RW25** 1800

6.6 NM

Visual Segment - Obstacles.

REIL Rwys 4 and 22 0 HIRL Rwy 4-22 🗓 MIRL Rwy 7-25 **0**

LNAV MDA 480-1 411 (500-1) 500-1 560-1 **C** CIRCLING 490 (500-1) 430 (500-1)

SUFFOLK EXEC (SFQ)RNAV (GPS) RWY 25

NA

NA

C

SUFFOLK, VIRGINIA Amdt 1B 02MAR17 5.3 NM -