

APP CRS

055°

Rwy Idg

6000

TDZE

670

Apt Elev

681

RNAV (GPS) RWY 6

MAURY COUNTY RGNL (MRC)

▼

▲

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Nashville Intl altimeter setting; increase all MDA 120 feet and increase LNAV Cat B visibility ¼ SM, Cats C and D visibility ½ SM, increase Circling Cat C visibility ½ SM.

MISSED APPROACH:

Climb to 3000 direct URSAW and hold.

AWOS-3 128.625	MEMPHIS CENTER 125.85 379.25	UNICOM 122.8 (CTAF) 0
-------------------	---------------------------------	--------------------------

The main chart displays the RNAV (GPS) RWY 6 approach. Key features include:

- Initial Descent:** From 3000 ft, a 145° turn leads to IJAPU, followed by a 235° turn to 3000 ft.
- Intermediate Descent:** From IJAPU, a 145° turn leads to CEMVU, followed by a 235° turn to 3000 ft.
- Final Descent:** From CEMVU, a 055° turn leads to ALWUB, followed by a 235° turn to 2500 ft.
- Final Approach:** From ALWUB, a 055° turn leads to DOXGU, followed by a 235° turn to 3000 ft.
- Final Descent:** From DOXGU, a 325° turn leads to RW06, followed by a 235° turn to 3000 ft.
- Obstacles:** Various obstacles are marked with their MSL altitudes: 1199, 1075, 1042, 729, 875±, 1335, 1216, 1449, 1335.
- Navigation Aids:** IJAPU, ALWUB, CEMVU, DOXGU, and URSAW are marked as navigation aids.
- Altitude Restrictions:** 3000 ft NoPT (5), 3000 NoPT (6.1), 3000 NoPT (5).

4 NM Holding Pattern

CEMVU

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 42).

3000

URSAW

3000

235°

055°

055°

2500

3.05°

TCH 40

6.1 NM

5.6 NM

RW06

055° to RW06

0.5% UP

0.4% UP

35

8000 x 100

CATEGORY	A	B	C	D
LNAV MDA	1340-1	670 (700-1)	1340-1¾ 670 (700-1¾)	1340-2 670 (700-2)
CIRCLING	1340-1 659 (700-1)	1360-1 679 (700-1)	1380-2 699 (700-2)	1620-3 939 (1000-3)

MIRL Rwy 6-24

REIL Rwy 6

REIL Rwy 24 0

COLUMBIA/MT.PLEASANT, TENNESSEE

MAURY COUNTY RGNL (MRC)

Orig-A 09SEP21

35°33'N-87°11'W

RNAV (GPS) RWY 6