



WAAS CH 63034 W19A	APP CRS 191°	Rwy Idg 3992 TDZE 19 Apt Elev 19
----------------------------------------	------------------------	-------------------------------------------------------------

RNAV (GPS) RWY 19

POINT HOPE (PHO) (PAPO)

<div><div>▼</div><div>▲ NA</div></div> <div>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). When local altimeter setting not received, procedure NA. DME/DME RNP-0.3 NA.</div>	MISSED APPROACH: Climb to 700 then climbing left turn to 2800 direct FENOM and hold.
----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------

AWOS-3P 118.325	ANCHORAGE CENTER 119.65 363.25	KOTZEBUE RADIO 122.25	CTAF 122.8 0
---------------------------	------------------------------------------	---------------------------------	------------------------



700	2800	FENOM	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00°/TCH 27°).			
*LNAV only		*0.9 NM to RW19	BABKE	JENSU	2400	
		RW19	1600	1600	191°	GP 3.00° TCH 40
		0.9 NM	3.9 NM	6 NM		
CATEGORY	A	B	C	D		
LPV DA	269-1		250 (300-1)			
LNAV/VNAV DA	269-1		250 (300-1)			
LNAV MDA	360-1		341 (400-1)			
CIRCLING	380-1 361 (400-1)	480-1 461 (500-1)	480-1½ 461 (500-1½)	580-2 561 (600-2)		